

AIR INDIRECT

Our range of internal expansion cylinders are engineered with precision and made with passion. The range saves space and fulfills the purpose of accommodating water expansion in the system without the added hassle of installing and maintaining an external expansion vessel.

INDIRECT AIR

Standard Diameter - 545mm							
Product Code	UOI120	UOI150	UOI170	UOI200	UOI250	UOI300	
Capacity (L)	120	150	170	200	250	300	
Height	A	915	1100	1224	1414	1722	1975
Cold Inlet	B	180	180	180	180	180	180
Heating Flow	C	180	180	180	186	201	201
Return	D	220	300	300	300	361	361
Control Stat	E	340	420	420	420	481	481
Immersion	F	270	350	350	350	411	411
Sec. Return	G	N/A	N/A	N/A	815	1036	1196
T&P Valve	H	508	695	770	915	1138	1303

Slimline Diameter - 478mm					
Product Code	UOIS120	UOIS150	UOIS170	UOIS200	
Capacity (L)	120	150	170	200	
Height	A	1240	1505	1680	1950
Cold Inlet	B	174	174	174	174
Heating Flow	C	199	199	199	199
Return	D	279	279	359	359
Control Stat	E	349	349	429	429
Immersion	F	329	329	409	409
T&P Valve	H	819	1008	1108	1298

